

Schneideisen UNC

Circular die UNC

HSS-G DIN EN 22568
(DIN 223 B)

98300 / 98800



Norm
Toleranz/*tolerance*
Material
Ausführung/*Type*

DIN EN 22568 (DIN 223 B)
2 A
HSS
Form B, vorgeschlitzt, geschlossen/
pre-slitted, closed

► Für Amerikanisches Grobgewinde

► Unified coarse thread

Einzeln/*Single*

Ø mm	Steigung <i>pitch</i>	Außen Ø <i>outside Ø</i>	€	Best-Nr. <i>order no.</i>
Nr. 2	55	18 x 5		98 302
Nr. 3	48	16 x 5		98 303
Nr. 4	40	20 x 5		98 304
Nr. 5	40	20 x 5		98 305
Nr. 6	32	20 x 7		98 306
Nr. 8	32	20 x 7		98 308
Nr. 10	24	20 x 7		98 310
Nr. 12	24	20 x 7		98 312
1/4"	20	20 x 7		98 801

Einzeln/*Single*

Ø mm	Steigung <i>pitch</i>	Außen Ø <i>outside Ø</i>	€	Best-Nr. <i>order no.</i>
5/16"	18	25 x 9		98 802
3/8"	16	30 x 11		98 803
7/16"	14	30 x 11		98 804
1/2"	13	38 x 14		98 805
9/16"	12	38 x 14		98 806
5/8"	11	45 x 18		98 807
3/4"	10	45 x 18		98 808
7/8"	9	55 x 22		98 809
1"	8	55x22		98810